

VVP9315DNIR

Colour Mono Vandal Resistant IR Dome Camera



■ CCD	1/3"
■ Resolution Colour	520 Lines
■ Sensitivity Colour	0.3 Lux
■ Sensitivity Mono	0.002 Lux IR LED On
■ Number of Infra Red LED	18
■ IR Range Metres	10m
■ Lens Size	3.6mm
■ Voltage	12V DC
■ Power Consumption	1A
■ Dimensions	140(Ø)x106(H)mm
■ Weight	Approx. 0.75Kg

The VVP range of vandal resistant dome cameras, provide the ideal surveillance solution for monitoring areas that are prone to attack, such as prisons, schools and car parks.

Enclosed in a stylish vandal proof dome housing, the VVP range features a Tri-axis mechanism to enable free rotation of the built in lens. With the ability to mount on the wall or ceiling and an on-screen display menu, the VVP range can be installed virtually anywhere with ease.

Featuring 18 in-built IR LEDs and IR Cut Filter, the VVP9315DNIR is able to view images in light levels of 0.002 Lux.

Other Features

- True Colour Mono
- Auto White Balance
- Auto Gain Control
- Back Light Compensation
- Flickerless
- Service Video Output
- 5 YEAR WARRANTY
- Tri-Axis Gimbal
- IP66
- On Screen Display Set-up
- Privacy Zones
- Digital Slow Shutter
- Digital Noise Reduction

Image Sensor	1/3" CCD
Effective Pixel	752H x 582V
Resolution	520 TV Lines
Shutter Speed	1/10,000 sec.
Video Output	VBS 1.0Vp-p(750hm Load)
Sync. System	Internal
Scanning System	2:1 Interlaced
S/N Ratio	48dB
Min. Illumination	0.3 Lux (Day Light), 0.002 Lux (IR LED On)
IR LEDs	18 IR LEDs with CDS Sensor
IR Distance	10m (Subject to site conditions)
Lens	3.6 mm fixed lens
Power Supply	DC 12V (750mA IR LED on)
Operating Temp.	-10°C ~ +55°C
Dimension	140mm(W) x 106mm(H)

Easy to Install



Full IR Capability at 90° Tilt



Enclosed in a discreet vandal proof dome housing, the VVP IR camera range features a tri-axis

gimbal to enable free rotation of the built in lens. With the ability to mount on the wall or ceiling, this high performance camera range can be installed virtually anywhere with ease.